

Juniper Networks NetScreen-500



The NetScreen-500 is a purpose-built, security system designed to provide a flexible, high performance solution for medium and large enterprise central sites and service providers. The NetScreen-500 security system integrates firewall, DoS, VPN and traffic management functionality in a low-profile, modular chassis. It provides high levels of total throughput for firewall and VPN plus support for virtual systems and security zones. Combined with a flexible and resilient hardware architecture incorporating modular physical interfaces, redundant power supplies, fans and high availability interfaces, the NetScreen-500 exceeds most enterprises' typical traffic conditions. It is well suited to match the peak load and strong deterrence requirements of the most demanding environments.

**Juniper Networks
NetScreen-500⁽¹⁾**

Maximum Performance and Capacity⁽²⁾

Firewall performance	700 Mbps
3DES performance	250 Mbps
Deep Inspection performance	300 Mbps
Concurrent sessions ⁽³⁾	250,000
New sessions/second	18,000
Policies ⁽⁵⁾	20,000
Interfaces	8 10/100 or mini-GBIC (SX or LX), 4 GBIC (SX or LX)

Mode of Operation

Layer 2 mode (transparent mode) ⁽⁵⁾	Yes
Layer 3 mode (route and/or NAT mode)	Yes
NAT (Network Address Translation)	Yes
PAT (Port Address Translation)	Yes
Policy-based NAT	Yes
Virtual IP	4
Mapped IP ⁽⁴⁾	4,096
Users supported	Unrestricted

Firewall

Number of network attacks detected	31
Network attack detection	Yes
DoS and DDoS protections	Yes
TCP reassembly for fragmented packet protection	Yes
Malformed packet protections	Yes
Deep Inspection firewall	Yes
Protocol anomaly	Yes
Stateful protocol signatures	Yes
Protocols supported	HTTP, FTP, SMTP, POP, IMAP, DNS
Number of application attacks detected w/DI	over 250
Content Inspection	Yes
External antivirus (Trend Micro)	Yes
Embedded antivirus (Trend Micro)	No
Malicious URL filtering	up to 48 URLs
External URL filtering (Websense)	Yes

VPN

Site-to-site VPN tunnels ⁽³⁾	up to 5,000
Remote access VPN tunnels	10,000 ⁽³⁾
Tunnel interfaces	up to 1,024
DES (56-bit), 3DES (168-bit) and AES encryption	Yes
MD-5 and SHA-1 authentication	Yes
Manual Key, IKE, PKI (X.509)	Yes
Perfect forward secrecy (DH Groups)	1,2,5
Prevent replay attack	Yes
Remote access VPN	Yes
L2TP within IPSec	Yes
IPSec NAT Traversal	Yes
Redundant VPN gateways	Yes
VPN tunnel monitor	Yes

Firewall and VPN User Authentication

Built-in (internal) database – user limit ⁽⁵⁾	up to 1,500
3rd Party user authentication	RADIUS, RSA SecurID, and LDAP
XAUTH VPN authentication	Yes
Web-based authentication	Yes

**Juniper Networks
NetScreen-500⁽¹⁾**

System Management

WebUI (HTTP and HTTPS)	Yes
Command Line Interface (console)	Yes
Command Line Interface (telnet)	Yes
Command Line Interface (SSH)	Yes, v1.5 and v2.0 compatible
NetScreen-Security Manager	Yes
All management via VPN tunnel on any interface	Yes
SNMP Full Custom MIB	Yes
Rapid deployment	No

Logging/Monitoring

Syslog (multiple servers)	External, up to 4 servers
E-mail (2 addresses)	Yes
NetIQ WebTrends	External
SNMP (v2)	Yes
Standard and custom MIB	Yes
Traceroute	Yes

Virtualization

Maximum number of Virtual Systems	0 Default, upgradeable to 25
Maximum number of security zones	8 default, upgradeable to 58
Maximum number of virtual routers	2 default, upgradeable to 27
Number of VLANs supported	100

Routing

OSPF/BGP dynamic routing ⁽³⁾	up to 8 instances each
RIPv2 dynamic routing ⁽³⁾	25 instances
Static routes	8,192
Source-based routing	Yes

High Availability (HA)

Active/Active	Yes
Active/Passive	Yes
Redundant Interfaces	Yes
Configuration synchronization	Yes
Session synchronization for firewall and VPN	Yes
Device failure detection	Yes
Link failure detection	Yes
Authentication for new HA members	Yes
Encryption of HA traffic	Yes

IP Address Assignment

Static	Yes
DHCP, PPPoE client	No
Internal DHCP server	Yes
DHCP Relay	Yes

PKI Support

PKI Certificate requests (PKCS 7 and PKCS)	Yes
Automated certificate enrollment (SCEP)	Yes
Online Certificate Status Protocol (OCSP)	Yes
Certificate Authorities Supported	
Verisign	Yes
Entrust	Yes
Microsoft	Yes
RSA Keon	Yes
iPlanet (Netscape)	Yes
Baltimore	Yes
DOD PKI	Yes

Juniper Networks NetScreen-500⁽¹⁾

Administration

Local administrators database	20
External administrator database	RADIUS/LDAP/SecurID
Restricted administrative networks	6
Root Admin, Admin, and Read Only user levels	Yes
Software upgrades	TFTP/WebUI/SCP/NSM
Configuration Roll-back	Yes

Traffic Management

Guaranteed bandwidth	Yes
Maximum bandwidth	Yes
Priority-bandwidth utilization	Yes
DiffServ stamp	Yes

External Flash

PCMCIA (PC Card)	Supports 96, 128, 440, and 512 MB
Event logs and alarms	Yes
System config script	Yes
NetScreen ScreenOS software	Yes

Dimensions and Power

Dimensions (H/W/L)	3.5/17.5/17 inches
Weight	27 lbs.
Rack mountable	19" standard, 23" optional
Power Supply (AC)	90 to 264 VAC, 100 watts
Power Supply (DC)	-36 to -72 VDC, 100 watts

Licensing Options: The NetScreen-500 is available with two licensing options to provide two different levels of functionality and capacity.

Advanced Models: The Advanced software license provides all of the features and capacities listed within this specsheet.

Baseline Models: The Baseline software license provides an entry-level solution for customer environments where features such as Deep Inspection™, OSPF and BGP dynamic routing, advanced High Availability, and full capacity are not critical requirements. The following table shows the features and capacities that are different than the Advanced models:

NetScreen-500 Baseline

Sessions	128,000
Concurrent VPN tunnels	1,000
Deep Inspection Firewall	N/A
OSPF/BGP	N/A
High Availability (HA)	Active/Passive only
NetScreen Security Manager	Future support

Certifications

Safety Certifications

UL, CUL, CSA, CB

EMC Certifications

FCC class A, BSMI Class A, CE class A, C-Tick, VCCI class A

Environment

Operational temperature: 32° to 122° F, 0° to 50° C

Non-operational temperature: -4° to 158° F, -20° to 70° C

Humidity: 10 to 90% non-condensing

MTBF (Belcore model)

6.5 years

Security Certifications (Advanced models only)

Common Criteria: EAL4

FIPS 140-2: Level 2

ICSA Firewall and VPN

Ordering Information

Product	Part Number
Juniper Networks NetScreen-500SP Bundles	
NetScreen-500 System SX GBIC, AC power	NS-500SP-GB1-AC
NetScreen-500 System SX GBIC, DC power	NS-500SP-GB1-DC
NetScreen-500 System SX dual-GBIC, AC power	NS-500SP-GB2-AC
NetScreen-500 System SX dual-GBIC, DC power	NS-500SP-GB2-DC
SP Systems include 25 Virtual Systems and 2 power supplies	
Juniper Networks NetScreen-500ES Bundles	
NetScreen-500 System 2 SX GBIC modules, 2 AC power supplies	NS-500ES-GB1-AC
NetScreen-500 System 2 SX GBIC modules, 2 DC power supplies	NS-500ES-GB1-DC
NetScreen-500 System 2 SX dual-GBIC modules, 2 AC power supplies	NS-500ES-GB2-AC
NetScreen-500 System 2 SX dual-GBIC modules, 2 DC power supplies	NS-500ES-GB2-DC
NetScreen-500 System 3 dual-10/100 modules, 2 AC power supplies	NS-500ES-FE1-AC
NetScreen-500 System 3 dual-10/100 modules, 2 DC power supplies	NS-500ES-FE1-DC
NetScreen-500 System 2 dual-10/100 modules, 1 AC power supply	NS-500ES-FE2-AC
NetScreen-500 System 2 dual-10/100 modules, 1 DC power supply	NS-500ES-FE2-DC
ES Systems include 0 Virtual Systems.	

Juniper Networks NetScreen-500 Baseline Systems

NetScreen-500 System 2 dual-10/100 modules, 1 AC power supply	NS-500B-FE2
NetScreen-500 System 2 SX GBIC modules, 1 AC power supply	NS-500B-GB1

Juniper Networks NetScreen-500 Virtual System Upgrades

Upgrade to 5 Virtual Systems	NS-500-VSYS-5
Upgrade from 5 to 10 Virtual Systems	NS-500-VSYS-10
Upgrade from 10 to 25 Virtual Systems	NS-500-VSYS-25

Every Virtual System includes one virtual router and 2 security zones, usable in the virtual or root system.

- (1) Performance, capacity and features listed are based upon the Advanced feature set running ScreenOS 5.0.0 and may vary with other ScreenOS releases. The Baseline model licensing option provides a subset of features as described in the table below. Actual throughput for Advanced and Baseline products may vary based upon packet size and enabled features.
- (2) Performance and capacity provided are the measured maximums under ideal testing conditions and may vary by deployment.
- (3) Shared among all Virtual Systems
- (4) Not available with Virtual Systems
- (5) The following features are not supported in Layer 2 (transparent mode): NAT, PAT, policy based NAT, virtual IP, mapped IP, virtual systems, virtual routers, VLANs, OSPF, BGP, RIPv2, Active/Active HA, and IP address assignment.



1194 North Mathilda Avenue Sunnyvale, CA 94089 USA
 Phone: 888-JUNIPER (888-586-4737) or 408-745-2000
 Fax: 408-745-2100

Copyright © 2004 Juniper Networks, Inc. All rights reserved.

Juniper Networks, the Juniper Networks logo, NetScreen, NetScreen Technologies, GigaScreen, and the NetScreen logo are registered trademarks of Juniper Networks, Inc. NetScreen-5GT, NetScreen-5XP, NetScreen-5XT, NetScreen-25, NetScreen-50, NetScreen-100, NetScreen-204, NetScreen-208, NetScreen-500, NetScreen-5200, NetScreen-5400, NetScreen-Global PRO, NetScreen-Global PRO Express, NetScreen-Remote Security Client, NetScreen-Remote VPN Client, NetScreen-IDP 10, NetScreen-IDP 100, NetScreen-IDP 500, GigaScreen ASIC, GigaScreen-II ASIC, and NetScreen ScreenOS are trademarks of Juniper Networks, Inc. All other trademarks and registered trademarks are the property of their respective companies.

Part Number: 110005-001 Apr 2004