

CONTENT PROTECTION SUITE APPLIANCE SPECIFICATIONS



Websense Content Protection Suite is available as software only or on purpose-built appliances. This flexible architecture allows for integration with application servers, database management, customer relationship management, enterprise resource planning and other key business infrastructure systems.

Appliance Configuration

Two types of appliances are available. The Enterprise Manager Appliance is pre-installed with Websense Content Protection Suite and includes management enforcement, PrecisID™ fingerprinting capabilities, and support for P-100 and P-500 Protector appliances. In a typical configuration, the Enterprise Management appliance would be installed inside the network and connected to any hub or switch. The appropriate Protector appliance(s) would be deployed transparently to sniff data by connecting to a network TAP or SPAN port on a switch or in in-line mode for monitoring and enforcement using Fail Open NICs over a layer 2 bridge or using integration with ICAP proxies.

Regulatory Compliance

Emissions Testing

- FCC Part 15 Class A
- Canada ICES-003 Class A
- Japan VCCI Class A
- EN55022 Level A & EN55024 (Immunity)
- CISPR-22

Safety Testing

- UL 60950
- CSA22.2 No 60950
- EN60950

Certification Marks

- cULus
- CE
- VCCI
- FCC PART 15
- SII

Interoperability

Web proxies

Microsoft ISA 2000, 2004 and 2006, Blue Coat SG, Cisco Content Engine, Network Appliance, Squid, Generic ICAP

Encryption gateways

PGP, PostX, ZixCorp, Global Certs, Tumbleweed, CipherTrust, generic encryption gateways

Mail Servers

Any SMTP or ESMTP based mail server

Databases

Any, using ODBC connectors

Document Management Systems

Any, using Open API (secured web service)

Websense Enterprise Manager Appliance Specifications		
Model	SX	MX
Form Factor	1U	1U
Purpose	Websense Manager Appliance for small enterprises and branch office networks	Websense Manager Appliance for head offices and enterprise networks
Memory	2G	4G
Number of Disks	4	4
RAID Option	Software	Hardware
Weight	54 lbs. (25.8 kg.)	54 lbs. (25.8 kg.)
Dimensions	1.7 x 17.2 x 26.7 in.	1.7 x 17.2 x 26.7 in.
Power Supply	Dual power supplies Input voltage: 100 to 240 VAC	Dual power supplies Input voltage: 100 to 240 VAC

Websense Protector Appliance Specifications		
Model	P-100	P-500
Form Factor	1U	1U
Purpose	Multi-protocol monitoring, enforcement and Discovery appliance for small enterprises and branch office networks	Multi-protocol monitoring, enforcement and Discovery appliance for enterprises networks
Memory	1G	2G
Disks	2	2
RAID Option	Software	Software
Boot Device	Flash	Flash
Interfaces	4	6
Fail Open Zones	1	2
Weight	54 lbs. (25.8 kg.)	54 lbs. (25.8 kg.)
Dimensions	1.7 x 17.2 x 26.7 in.	1.7 x 17.2 x 26.7 in.
Power supply	Dual power supplies Input voltage: 100 to 240 VAC	Dual power supplies Input voltage: 100 to 240 VAC